

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS


IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: B60R 9/045	A1	(11) International Publication Number: WO 97/19832 (43) International Publication Date: 5 June 1997 (05.06.97)
(21) International Application Number: PCT/US96/19012 (22) International Filing Date: 26 November 1996 (26.11.96) (30) Priority Data: 08/565,410 30 November 1995 (30.11.95) US (71) Applicant: ADVANCED ACCESSORY SYSTEMS L.L.C. [US/US]; Suite 200, 12900 Hall Road, Sterling Heights, MI 48313 (US). (72) Inventors: CRONCE, Gary, M.; 1312 Twenty-Third Street, Port Huron, MI 48060 (US). STAPLETON, Craig, A.; 995 Muer Street, Troy, MI 48084 (US). PRASATEK, Craig, R.; 888 Dahlia Lane, Rochester Hills, MI 48307 (US). (74) Agent: COPPOLA, Joseph, V., Sr.; Rader, Fishman & Grauer P.L.L.C., Suite 140, 1533 North Woodward Avenue, Bloomfield Hills, MI 48304 (US).		(81) Designated States: CA, MX. Published <i>With international search report.</i>
(54) Title: SPLIT STANCHION ARTICLE CARRIER (57) Abstract An article carrier (10) for mounting to a vehicle body panel is formed by a cross bar (40, 42) connecting longitudinal rails (14, 16). The cross bar (40, 42) is made of a cross rail (48) and stanchions (44, 46) which support the cross rail (48) for displacement along and locking engagement with the longitudinal rails (14, 16). The split stanchions (44, 46) are formed of first and second jaw members (64, 66) and one of the jaw members is carried by a shelf on the other jaw member and displaced along the shelf by a retainer (68). The retainer (68) is manipulated by an actuator (70) preferably in the form of a rotary knob (76) which is selectively engageable with a nut (78). The nut (78) is threadably engaged on a threaded shaft that is engaged in an insert in the one of jaw parts and extending through the other jaw part. At least one of the jaw parts (64, 66) includes an engagement surface for locking the stanchion (44, 46) to the rail (16) when the retainer (68) has moved the jaws (64, 66) to the closed position. Conversely, the retainer (68) separates engagement surfaces from the longitudinal rail (16) when the jaw parts (64, 66) are moved to an open position, in which the cross rail (48) is displaceable along or removable from the longitudinal rail (16).		



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

WO 97/19832

PCT/US96/19012

SPLIT STANCHION ARTICLE CARRIER

Field Of The Present Invention

The present invention relates generally to vehicle luggage carriers and, more particularly, to a
5 movable crossbar detachably secured to a pair of spaced longitudinal rails.

Background Art

There are many previously known vehicle
mounted luggage and article carriers. Such article
10 carriers commonly include a pair of spaced apart roof rails affixed to a body panel of the automobile such as the roof top or rear deck panels of the vehicle. At least one, and usually two, crossbars extend transversely across the longitudinal rails. The
15 crossbars may be directly secured to or carried by the longitudinal rails.

In addition, it has also been known to raise the crossbars above the top of the rails by stanchions that support the crossbar in an elevated position.
20 However, crossbars which are permanently secured to the longitudinal rails do not permit the carrier to be adjusted for differing load configurations and article carrying capacities.

Although some crossbars and stanchions are
25 designed for detachable mounting to the longitudinal rails, some of the detachable mounting mechanisms are complicated or difficult to operate. For example, one previously known form of stanchion is disclosed in U.S.

WO 97/19832

PCT/US96/19012

-2-

Patent No. 4,270,681, which discloses an article carrier with a slidable bracket. The rails include an open topped channel having a reduced access opening. The bracket includes a base section slidably movable in the channel that retains the bracket within the channel of the rail. The bracket and a cross rail mounted to the bracket may be removed from the track only if the bracket is slid all the way to the open end at the farthest extent of the longitudinal rail. Moreover, the bracket can be locked in position along the longitudinal rail by a key which is threadably secured to a rotatable disk. As the disk is rotated, the key is urged into engagement with the base of a track to urge the base section of the bracket up against the top wall of the restricted channel opening in the longitudinal rail. Such a structure stresses the material forming the reduced opening for the channel in the longitudinal rail.

Another known type of stanchion structure for locking the crossbar in a fixed position along a longitudinal rail is shown in U.S. Patent Nos. 4,162,755, 4,274,570 and 4,323,182. These patents disclose a stanchion element carried on top of a channeled longitudinal rail. The stanchion receives a through bolt carried by a locking plate that is entrained within the rail channel. The bolt extends through the stanchion member for engagement with a rotatable wheel for tightening the bolt and pressing the top wall of the rail including the restricted channel opening between the plate and the stanchion element. However, like the previously discussed stanchion attachment, the threaded bolt must be disengaged and removed from one of the threaded apertures in the wheel or the lower plate so that the parts may be separated

WO 97/19832

PCT/US96/19012

-3-

for removal of the stanchion from the longitudinal rail. Alternatively, with the clamping device loosened, the stanchion and crossbar must be slid completely to one longitudinal end of the longitudinal rail to remove the stanchion and crossbar from the rack in the absence of
5 complete disassembly of the bolt retaining mechanism.

Another known luggage carrier construction is shown U.S. Patent No. 4,487,348 discloses an end bracket for attaching a cross rail to a side rail of a luggage
10 carrier. The bracket includes a first element and a second element pivotally connected to the first element. The first element also includes a threaded insert adapted to receive a bolt carried by the second element and having an enlarged head for manual rotation of the
15 threaded stem. A protruding portion of the rail is inserted between the first and second elements which are then pressed against the protrusion by the rotary locking member. However, the enlarged head is confined beneath the stanchion and cross rail and inside of the
20 side rail in a confined area that is difficult to reach and maneuver the threaded knot stem. Moreover, the two elements are made of substantially different materials and can have substantially different responses to environmental conditions and weather changes. In
25 addition, the side rails must be specially constructed to include a protrusion or a shape which can be wholly confined within jaws shaped to receive the entire cross section of the rails taught in the embodiments disclosed in the patent.

30

Summary Of The Invention

The present invention overcomes the above-mentioned disadvantages by providing a crossbar with a

WO 97/19832

PCT/US96/19012

-4-

stanchion that is split to form a first jaw connected to a cross rail, a second jaw displaceably carried by a shelf on the first jaw, and a retainer for detachably clamping the stanchion against the rail by an engagement surface. In general, this shelf permits the pressing surfaces of the jaws to be separated without disassembling all or part of the stanchion. Moreover, the retainer clamps the jaws in response to manual tightening of the clamp, preferably by rotating a handle exposed for easy access from the stanchion.

Another particularly advantageous feature of the present invention is that the stanchion may be removed from the longitudinal or side rail when the jaws are unclamped. In addition, the unclamped condition of the stanchion is identified by an indicator exposed exteriorly of the stanchion. In the preferred embodiment, the indicator comprises a button that protrudes outwardly from a cavity in the stanchion, and the protruding surface is provided with visible indicia such as an orange color to provide a warning to the operator that the jaws are still separated and the crossbar stanchion is not secured. Preferably, mating cavities are formed in the first and second jaws to house a lever mechanism for displacing the button outwardly as the second jaw is moved to separate from the first jaw carrying the cross rail.

In the preferred embodiment, an engagement surface on one of the jaws engages a rail portion when the jaws are in their clamped or closed position. In one embodiment, an engagement surface on one jaw part is received within an upper channel opening of the longitudinal rail while the pressing surface on the other jaw presses against the opposite side of the wall

WO 97/19832

PCT/US96/19012

-5-

defining the channel. In yet another embodiment, the longitudinal rail includes a side opening and an engagement surface on one of the jaw parts extends into a detent such as an opening in the side wall of the longitudinal rail. In addition, the preferred embodiment shows an improved clamping arrangement in which a flange extends beneath the longitudinal rail when the jaws are in the clamped or closed position.

As a result, the present invention provides a crossbar structure in which the stanchion can be detachably secured to a longitudinal rail without disassembly of the clamp or parts of the stanchion. Moreover, one of the jaw parts is carried by the other jaw part so as to retain corresponding positions and limited directional movement when the jaws have been moved to or released or open position.

The present invention includes a stanchion structure defined by a first jaw and a second jaw carried by the first jaw on a shelf and, a retainer for displacing the jaws against the longitudinal rail for contact by an engaging surface. The engaging surface may be smaller than the entire periphery of the side rail. The present invention also provides a crossbar structure in which an indicator designates the open or unclamped position of the jaws by the readily perceived indicator. In addition, while the pressing surfaces of the jaws can be configured to conform with a wide variety of longitudinal rail contours, the rail is readily removed from a support position along the longitudinal rail without displacement toward an end of the rail. Moreover, the present invention provides a stanchion that can be manually clamped with ease by an operator without complicated alignment or special tools

WO 97/19832

PCT/US96/19012

-6-

required to actuate the retainer that clamps the jaws against the longitudinal rail.

Other features and advantages of the present invention will be apparent from the following detailed description taken in connection with the accompanying drawings.

Brief Description Of The Drawings

The present invention will be more clearly understood by reference to the following detailed description of a preferred embodiment when read in conjunction with the accompanying drawing in which like reference characters refer to like parts throughout the views and in which:

FIGURE 1 is a top perspective view of the article carrier of the present invention;

FIGURE 2 is a side, partially cross-sectioned view of a split stanchion of the present invention shown in the secured position;

FIGURE 3 is a side, partially cross-sectioned view of a stanchion of the present invention shown in the disengaged position;

FIGURE 4 is a cross-sectional view taken along lines 4-4 of Figure 3 of the indicator linkage of the present invention;

FIGURE 5 is a side, partially cross-sectioned view of an alternative embodiment of a split stanchion

WO 97/19832

PCT/US96/19012

-7-

of the present invention showing the stanchion in the engaged position; and

FIGURE 6 is a side, partially cross-sectioned view of the alternative embodiment of Figure 5 shown in the disengaged position.

While only examples of the present invention has been disclosed, it should be understood that other forms of Applicant's invention may be had, all coming within the spirit of the invention and scope of the appended claims.

Detailed Description of the Preferred Embodiment

Illustrated in Figure 1 is an article carrier 10 of the present invention. The article carrier 10 is shown affixed atop an automobile roof top 12. The article carrier 10 also includes a pair of parallel roof rails 14 and 16. Preferably, each roof rail 14 and 16 generally includes a track 18 extending along the rails 14 and 16. Although each rail is shown including a channel 30, the track 18 may be formed by only a part or all of the rail walls forming the channel 30. Generally, each roof rail 14 and 16 includes a side wall 24 including a plurality of spaced apart detents 20, each detent preferably comprising an opening 22 in the rail wall 24 and preferably being positioned in longitudinal registration with a detent 20 on the opposite rail.

In the embodiment shown in Figures 1 through 3, the track 18 of each of the roof rails 14 and 16 further includes a first track segment 26 and a second track segment 28. As shown in Figures 2 and 3, the

WO 97/19832

PCT/US96/19012

-8-

first track segment 26 is preferably defined by a wall portion defining the arcuate channel 30. The channel 30 includes an enclosed cavity portion 32 beneath opposing upper lip portions 34 and 36. The rails 14 and 16 are
5 formed in the preferred embodiment of a roll formed sheet of material such as aluminum or steel but they could also be formed of an extruded material, for example aluminum. The rails mounted by end caps 60 and center foot 62 to raise the rails above the roof panel
10 12.

Still referring to Figures 2 and 3, second track segment 28 extends from lip portion 34 along wall 24. In the preferred embodiment of the present invention, detents 20 are disposed within the second
15 track segment 28. It is preferred that each detent comprise an opening 22 defined within elongate wall segment 38.

A pair of crossbars 40 and 42 are shown
20 extending from roof rail 14 to roof rail 16. In the embodiment shown in Figure 1, each crossbar 40 and 42 generally comprises a pair of split stanchions 44 and 46 which are generally right and left hand versions of a similar structure, shown in more detail in Figures 2 and
25 3 with reference to stanchion 46, and a cross rail 48. In the preferred embodiment, the cross rail 48 is manufactured from a hollow member 50 for example, steel tube, having a generally rectangular cross section, although other materials can also be used depending on
30 load support limitations.

The cross rail 48 is bolted or otherwise connected to and extends from split stanchion 44 to split stanchion 46. Each split stanchion preferably

WO 97/19832

PCT/US96/19012

-9-

includes a connecting section 52 which is adapted to be fastened to cross rail 48 by a pair of common screw fasteners 50. The screw fasteners are received within registering bores 56 and 58 within the connecting section 52 and the cross rail 48 respectively. Preferably, the connecting member 52 is formed as part of one of the jaws 64 and 66 described below.

As shown in Figure 2, a split stanchion structure 44 or 46 according to the present invention is typically illustrated by the details disclosed in the sectional of view stanchion 46. The stanchion comprises a first jaw 64 and a second jaw 66 made of metal or plastic such as Dupont Zytel ST801. The jaws are displaceably connected together by a retainer 68 comprising a threaded shaft 72 and an actuator 70. The shaft 72 is carried in an insert 74 mounted in the jaw 66. A nut is threadably engaged on the bolt 72 to actuate engagement of the jaws 64 and 66 to the closed position shown in Figure 2. The nut is tightened by an actuator 70 comprising an enlarged rotary knob 76 that carries the nut at 78.

As the rotary knob is turned to tighten the nut 78 against the jaw 64, the jaws 64 and 66 tighten or close engagement surfaces against mating portions of the rail. In particular, engagement surfaces on the jaws may engage portions of the track 18 formed on the longitudinal rail 16. The jaw 66 includes a cavity 80 (Figure 3) that receives a side wall of the rail 16. The cavity 80 is defined by a wall portion 82 adapted to mate with track portion 28 and including projections 84 adapted to be received in the openings 22.

WO 97/19832

PCT/US96/19012

-10-

In addition, as also shown in Figures 2 and 3, the first track segment 26 is detachably engaged between engagement surfaces of the jaw 64 and the jaw 66. In particular, the lip 34 may be entrapped between engagement surfaces of the jaws 64 and 66 at the same time the engagement surface 82 engages the track portion 28.

The other end of the jaw 66 includes a cavity 86 registering with a cavity 88 in the jaw 64. The cavity 88 continues from a bore 90 exposed exteriorly of the jaw 64 and positioned to expose a button 92 carried in the bore 90. Button 92 includes a stem pivotally secured to a lever. The lever 93 in turn is pivotally secured by a pin 96 mounted in the jaw 64 across cavity 88. Another pin 98 is mounted in the jaw 66 to extend across the opening 86. The pin 98 is carried in an elongated slot 100 in the end of the lever 93 so that movement of the jaw 66, limited to the direction of the arrow 102 shown in Figure 3 as discussed below, will move the pin so that the lever pivots about the pivot pin 96 to expose the button 92 exteriorly of the stanchion 46. The outside surface 95 may be colored with a bright color, while the end surface 97 of button 92 remains matched with the color of the surface 97.

As best shown in Figure 4, the indicator 91 (Figure 2) is loaded in an expanded cavity 88. Moreover, the jaw 64 provides a shelf 104 receiving an expanded or T-shaped head surface 106 on the jaw part 66 to form a shelf which maintains the integrity of the split stanchion 46 during displacement of the jaws 64 and 66 and which limits the direction of movement to provide directional control over the displacement between the jaws.

WO 97/19832

PCT/US96/19012

-11-

In the closed position, it will be noted that the pin 98 as shown in an upper portion of the slot 100 when the jaws in its closed position shown in Figure 2. Conversely, when the jaws are displaced apart as shown in Figure 3, the pin 98 is displaced toward the bottom of the slot 100 as the lever 93 is pivoted about the pin 96 to expose the button 92.

The actuator 70 may be lockably retained upon the shaft 72 in a well known manner, for example a lock retainer made available by King Roof Industrial Co. Ltd. which is operable by a key 110. Rotation of the key in one direction permits the handle 76 to be freely rotated about the nut 78 without displacing the nut 78 in threaded engagement along the shaft 72. Conversely, a further turn of the key locks the handle for rotation with the nut so that rotational of the handle moves the nut along the threaded shaft.

An alternative version of a split stanchion is shown in Figures 5 and 6. Unlike the rails 14 and 16 shown in Figure 1, a longitudinal rail 130 includes a track 132 comprising a recessed wall 134 including the openings 22 and an abutment corner 136. Corner 136 is pressed between engagement surfaces on the jaw member 144 and jaw member 146. The split stanchion 46 is attached with a connecting portion 52 in much the same way as the version shown in Figures 2 and 3. Similarly, the jaws 144, 146 are displaced by a retainer 68 as previously discussed and operated by an actuator 70 as shown and described in regard to Figures 1-4. Moreover, the embodiment shown in Figures 5 and 6 does not show the indicator 91 although it is to be understood that the indicator arrangement is equally applicable to this

WO 97/19832

PCT/US96/19012

-12-

version of split stanchion as well as other stanchion constructions according to the present invention.

As best shown in Figure 6, a surface 140 extending in a direction of displacement for the jaws may be used to form a shelf whereby one of the jaw parts carries the other jaw. While the jaw 144 is shown including the shelf surface 140 to receive the mating surface 142 of the jaw 146, either jaw part may be formed with a connecting portion 52 as described in this disclosure or another mounting means for securing the stanchion to the cross rail.

Having thus described the present invention, many modifications thereto will become apparent to those skilled in the art to which it pertains without departing from the scope and spirit of the invention as defined in the appended claims.

WO 97/19832

PCT/US96/19012

-13-

WHAT IS CLAIMED IS:

1. A cross bar for a vehicle panel mounted article carrier with longitudinal rails comprising:

a cross rail;

5 first and second stanchions for supporting said cross rail on the rails;

at least one of said first and second stanchions comprising a first jaw secured to said crossbar;

10 a second jaw, carried by a shelf in said first jaw, at least one of said jaws including an engagement surface for mating with a rail portion;

a retainer for displacing said jaws along said shelf to and between a closed position at which said first jaw and said second jaw enclose at least a mating portion of one of the longitudinal rails with said engagement surface for attachment to said one longitudinal rail and an open position separating said first jaw from said second jaw and said engagement surface from said mating rail portion; and

20 an actuator for manually controlling said retainer.

2. The invention as defined in claim 1 wherein said actuator comprises a rotary handle.

25 3. The invention as defined in claim 1 wherein said retainer comprises a bolt carried by one of said first and second jaws and threadably engaged in the other of said first and second jaws.

30 4. The invention as defined in claim 3 wherein said actuator includes a rotary handle.

WO 97/19832

PCT/US96/19012

-14-

5. The invention as defined in claim 4 wherein said rotary handle includes a nut.

6. The invention as defined in claim 5 wherein said handle includes a lock for selectively
5 engaging said nut with said bolt.

7. The invention as defined in claim 6 wherein said lock is actuated by a removable key.

8. A crossbar for a vehicle panel mounted article carrier with longitudinal rails comprising:
10 a cross rail;
first and second stanchions for supporting said cross rail on the longitudinal rails;
at least one of said first and second stanchions comprising a first jaw secured to said
15 crossbar;
a second jaw, carried by a shelf in said first jaw, at least one of said jaws including an engagement surface for mating with a rail portion;
a retainer for displacing said jaws along said
20 shelf to and between a closed position at which said first jaw and said second jaw enclose at least a mating portion of one of the longitudinal rails with said engagement surface for attachment to said one longitudinal rail, and an open position separating said
25 first jaw from said second jaw and said engagement surface from said mating rail portion; and
an indicator for exposing indicia exteriorly of said at least one stanchion when said retainer secures said jaws in said open position.

WO 97/19832

PCT/US96/19012

-15-

9. The invention as defined in claim 8 wherein said indicator comprises a button slidably carried in an exposed bore in one of said jaws.

5 10. The invention as defined in claim 9 wherein said button enlarges a first lever end, said lever is pivoted at a point intermediate said first end and a second end, and said second end is displaced by engagement with the other of said jaws.

10 11. A split stanchioned article carrier for mounting on a vehicle body panel comprising:

a first longitudinal rail and a second longitudinal rail;

first and second stanchions for supporting each said cross rail;

15 at least one of said first and second stanchions comprising a first jaw secured to said crossbar;

a second jaw, carried by a shelf in said first jaw, at least one of said jaws having an engagement surface for mating with a rail portion;

20 a retainer for displacing said jaws along said shelf to and between a closed position at which said first jaw and said second jaw enclose at least a mating portion of one of said longitudinal rails with said engagement surface for attachment to said one longitudinal rail, and an open position separating said first jaw from said second jaw and said engagement surface from said mating longitudinal rail portion; and

25 an actuator for manually controlling said retainer.

12. The invention as defined in claim 11 wherein said longitudinal rail includes a side channel,

WO 97/19832

PCT/US96/19012

-16-

and wherein said engagement surface is received in said side channel.


13. The invention as defined in claim 11 wherein said longitudinal rail includes a top channel
5 and said engagement surface is received in said top channel.

14. The invention as defined in claim 11 wherein said engagement surface comprises a flange engageable beneath said longitudinal rail.

WO 97/19832

1/4

PCT/US96/19012




WO 97/19832

PCT/US96/19012

3/4



FIG 4



WO 97/19832

4/4

PCT/US96/19012



INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 96/19012

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B60R9/045

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 B60R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 95 20504 A (MASCOTECH) 3 August 1995 see the whole document -----	1-14

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

10 March 1997

Date of mailing of the international search report

20.03.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Knops, J

INTERNATIONAL SCH REPORT

Information on patent families

International Application No

PCT/US 96/19012

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9520504 A	03-08-9	EP 0741650 A	13-11-96